

(19)



European Patent Office

Office européen des brevets



(11)

EP 0 923 965 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

23.06.1999 Bulletin 1999/25

(51) Int Cl.<sup>6</sup>: A63C 17/00, A43B 5/16,

A63C 17/06

(21) Application number: 98124312.4

(22) Date of filing: 21.12.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 22.12.1997 US 995759

(71) Applicant: ROLLERBLADE, INC.

Eden Prairie, Minnesota 55344 (US)

(72) Inventor: The designation of the inventor has not  
yet been filed

(74) Representative: Bosotti, Luciano et al

c/o JACOBACCI &amp; PERANI S.p.A.

Corso Regio Parco, 27

10152 Torino (IT)

(54) Roller skate boot comprising a cuff buckling device

(57) A cuff buckling apparatus to ease the buckling of an in-line skate boot having a cuff is provided. The in-line skate (20) includes a boot (22) having front and back portions corresponding to the front and back of a skater's leg, and medial and lateral portions corresponding to the medial side and lateral side of the skater's leg respectively. A leg cuff (40) encases the back, medial and lateral portions of the boot (22), and includes a cuff flap (46) originating proximate the medial portion of the boot (22). The cuff flap (46) has sufficient length to cross the front portion of the boot (22) when folded over the front of the boot (22). A buckle lever (48) is coupled to the leg cuff (40) proximate the lateral portion of the boot (22), and a buckle strap (52) is mounted to the buckle lever (48). A buckle strap latching mechanism (50) attaches to the cuff flap (46), and engages the free end of the buckle strap (52). The leg cuff (40) is tightened around the skater's leg upon actuating the buckle lever (48).




FIGURE 4




FIGURE 1






FIGURE 3




FIGURE 4




FIGURE 5